eM ketplace

Onder No: 2269 Dt 30:12.2019 Generated Date:10-Dec-2019

Contract No: GEMC-511687771445334

am a Details

State Government

de nenti Odisha

Skill Development and Technical Education Department.

sation

Directorate Of Technical Education And Training , Odisha ,

e Zone: Cuttack

Buyer Details

Prasanna Kumar Senapati Name:

Designation:Training Officer Presanna Senapati

Contact

674-2390617-

No.:

Email ID: prasanna.itibbsr@gov.in

GSTIN: 21BBN100271F1D9

GOVT ITI BHUBANESWAR, Near Governer House

BhubaneswarNayapalli Unit B. Address:

KHORDA, ODISHA-751012, India

90%

inancial Approval Detail

Designation of Administrative Approval: PRINCIPAL INDUSTRIAL TRAINING INSTITUTE, BHUBANESWAR

Designation of Financial Approval : DDO

Seller Details

Company Name:

Contact No.:

VINEET ENGINEERS

VINITENGG1978@GMAIL.COM 279 SECOND FLOOR GALI NO.5, DURGAPURI EXT, DELHI,

Email ID: Address:

East Delhi, DELHI-110093, -

Product Details

H	Item Description	Category Name	Model	Ordered Quantity	Unit	Price (Inclusive of all Duties and Taxes in INR)
1.4	RESPIRATION RATE	Digital Media Evaluation Educational Kit	SCIENTECH 2353	1	pieces	16,330
	MONITOR KIT	Educational Att				16,330

Total Order Value (in INR)

Consignee Detail

	signee Detail Consignee	Item	Quantity	Expected Delivery Date
1	Prasanna Kumar Senapati Training Officer Prasanna Senapati Landline-674-2390617- prasanna.itibbsr@gov.in GOVT ITI BHUBANESWAR,Near Governer House BhubaneswarNayapalli Unit B, KHORDA, ODISHA-751012, India	RESPIRATION RATE MONITOR KIT	1	25-Dec-2019

Product Specification for RESPIRATION RATE MONITOR KIT

Sub-Spec		Value
Specification FEATURES AND FUNCTIONALITY PARAMETERS OF DIGITAL MEDIA EVALUATION EDUCATIONAL KIT	Name of the Digital Media Evaluation Educational Kit	720MHz DM642
emory	Memory capacity of Flash memory in MB	6.37
	Memory capacity of SDRAM in MB	5.06
	Memory capacity of EEPROM in KB	5.07
ideo Capture	Number of Female RCA connectors for composite video input	1
	Number of Female S-Video connector for component (Y-C) video input	1
Bhubaneswar	Availability of Video Decoder for displaying the video	No

	output or HDTV)	
deo Display	Number of Female S-Video connector for RGB monitor output	1
	Number of Female 15-pin VGA connector for RGB monitor output	1
	Availability of On-Screen Display support (OSD FPGA)	No.
	Number of Line In (stereo) Channel	1 1
AUDIO	Number of sampling pulses for Line In (Sreeo) channel	1
	Number of Line Out (stereo) Channel	1
	Number of Microphone Input (mono)	1
	Availability of 10BASE-T or 100 Base-TX using single RJ-45 connector	No RTIFICATION A
	Availability of Dual UART interface	No
Connectivity	Availability of Daughter card interface for video port and memory bus expansion	No
	Availability of 14-pin JTAG for external emulation hardware support	No 91
	"Availability of 60-pin next generation emulation header for advanced emulation features such as Tracing, High Speed Real-Time Data Exchange"	No
	Availability of Boot mode selection via switches	No
Emulation, Power, Miscellaneous	Availability of push button for reset	No
	Number of User defined LEDs and GPIOs (General-purpose input/output)	1 SENER
	Availability of On-board switching voltage regulators for adjustable DSP core voltage in volts	1
	Availability of On-board switching voltage regulators for fixed DSP core voltage in volts	1.2
	Availability of installation support for CCStudio v2-2 and v3-0 in DM642 EVM Software	No
	Availability of DM642 chip support package in EVM software	No
	Availability of DSP/BIOS kernel support for the peripheral devices	No
	Drivers included in Device Driver Kit (DDK) for DM642	Video capture and Displa drivers for DM642 EVM
	Availability of eXpressDSP Reference Framework 5	No
DM642 EVM (Digital Media Evaluation Module) Software	Availability of Video Application Demos including source code for	Capture/Display pass-th demos(Composite/S-Vid
	Availability of Streaming Media Executable Demos(with object code libraries) Video	in/Out)
	Availibility of H-263, MPEG-2 video and JPEG	No
	Availibility of TCP/IP Networking stack (Client/ Configuration) Availibility of Network C	No
	The Work Camera Dome	No
	Provision of CD (soft copy) with sample project code, programmer software, useful Standard Accessories in the control of the	No
	Todaties included to the	No
	y sound of other additional accessories	Cables
		NA
OPERATING CONDITION	Input power supply frequency in Hertz Indicate operating input power.	230
	Indicate operating input power supply requirements Minimum Operating tempature for Digital Media Evaluation Kit in de	50